NSN 5330-00-246-8168

Gasket - Page 1 of 1

Mil-c-6183 spec.



View Online at https://aerobasegroup.com/nsn/5330-00-246-8168

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| 0.120 inches |
| Overall Length: |
| 1.188 inches |
| Overall Width: |
| 1.188 inches |
| Aperture Diameter: |
| 0.938 inches |
| Outside Corner Radius: |
| 0.062 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 0.906 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 0.906 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.141 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.141 inches |
| Cross-sectional Thickness: |
| 0.031 inches |
| Bolt Hole Quantity: |
| 4 |
| Hardness Rating: |
| 70.0 shore durometer a and 85.0 shore durometer a |
| Material: |
| Rubber synthetic and cork |
| Material Specification: |
| Mil-c-6183, type 1, cl 1, gr c military specification all material responses |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| Mil-std (military Standard): |