NSN 5330-00-253-7173

Gasket - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5330-00-253-7173

Solid single or composition Hole Diameter: 0.250 inches Overall Midth: 5.870 inches Overall Width: 5.870 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 3.50 shore durometer a and 45.0 shore durometer a Material Specification: Asten d2000 5bg400abe/2 assn standard all material responses Style Designator:	
Hole Diameter: 0.250 inches Overall Length: 8.250 inches Overall Width: 8.250 inches Overall Width: 8.250 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Cutside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 3.50 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astin d2000 5bg400abef2 assn standard all material responses Style Designator:	Cross Sectional Shape:
0.250 inches Overall Length: 8.250 inches Overall Width: 5.870 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Cutside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.570 inches Unside Edge To Bolt Hole Center Distance Along Length: 1.570 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.570 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 3.5.0 shore durometer a and 45.0 shore durometer a Material Specification: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abel2 assn standard all material responses Style Designator:	
Overall Length: 8.250 inches Overall Width: 5.870 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 1.360 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 8.5.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	
8.250 inches Overall Width: 5.870 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 1.560 inches Custed Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 3.5.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	
Overall Width: 5.870 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.570 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 3.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	-
5.870 inches Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Width: 6.000 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Cutside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.570 inches Couside Edge To Bolt Hole Center Distance Along Length: 1.570 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	
Inside Corner Radius: 0.250 inches Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Cutside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.570 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	
Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	5.870 inches
Outside Corner Radius: 0.870 inches Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Inside Corner Radius:
Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	0.250 inches
Aperture Width: 4.620 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Eetween 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Outside Corner Radius:
Ale20 inches Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	0.870 inches
Aperture Length: 6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Aperture Width:
6.000 inches Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	4.620 inches
Center To Center Distance Between Bolt Holes Along Width: 2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Aperture Length:
2.750 inches Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	6.000 inches
Center To Center Distance Between Bolt Holes Along Length: Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Center To Center Distance Between Bolt Holes Along Width:
Between 2.740 inches and 2.760 inches Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	2.750 inches
Outside Edge To Bolt Hole Center Distance Along Width: 1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Center To Center Distance Between Bolt Holes Along Length:
1.560 inches Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Between 2.740 inches and 2.760 inches
Outside Edge To Bolt Hole Center Distance Along Length: 1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Outside Edge To Bolt Hole Center Distance Along Width:
1.370 inches Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	1.560 inches
Cross-sectional Thickness: 0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Outside Edge To Bolt Hole Center Distance Along Length:
0.060 inches Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	1.370 inches
Bolt Hole Quantity: 10 Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Cross-sectional Thickness:
Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	0.060 inches
Hardness Rating: 35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Bolt Hole Quantity:
35.0 shore durometer a and 45.0 shore durometer a Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	10
Material: Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Hardness Rating:
Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	35.0 shore durometer a and 45.0 shore durometer a
Material Specification: Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Material:
Astm d2000 5bg400abef2 assn standard all material responses Style Designator:	Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu
Style Designator:	Material Specification:
	Astm d2000 5bg400abef2 assn standard all material responses
Non-circular	Style Designator:
Tron on out an	Non-circular
Shelf Life:	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:
	
Demilitarization:	Demilitarization:

NSN 5330-00-253-7173

Gasket - Page 2 of 2



Fiig:

A032a0