NSN 5330-00-290-9838

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-290-9838

Cross Sectional Shape: Cloth and synthetic rubber, nonmetallic material Hole Diameter: 0.344 inches Overall Length: Between 7.865 inches and 7.885 inches Overall Width: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.322 inches Aperture Vidth: Between 0.302 inches and 2.635 inches Aperture Length: Between 6.365 inches and 2.635 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit of Measure: - Demilitarization: No Fig: A032a0		
Hole Diameter: 0.344 inches Overall Length: Between 7.865 inches and 7.885 inches Overall Width: Between 4.115 inches and 4.135 inches Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Corse-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 7.0. shore durometer a and 85.0 shore durometer a Material: Nubber synthetic and plastic polyamide Style Designator: Non-circular Na Nametaria: Na Dun-circular Style Designator: <th>Cross Sectional Shape:</th> <th></th>	Cross Sectional Shape:	
0.344 inches Overall Length: Between 7.865 inches and 7.885 inches Overall Width: Between 4.115 inches and 4.135 inches Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.325 inches Aperture Length: Between 6.365 inches and 2.635 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Bott Hole Quantity: 12 Hardness Rating: 7.5.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	•	
Overall Length: Between 7.865 inches and 7.885 inches Overall Width: Between 4.115 inches and 4.135 inches Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Corss-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 7.5.0 shore durometer a and 85.0 shore durometer a Material: Nubber synthetic and plastic polyamide Style Designator: Non-circular Sheff Life: Na Unit Of Measure: <		
Between 7.865 inches and 7.885 inches Overall Width: Between 4.115 inches and 4.135 inches Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 0.322 inches Aperture Length: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Uidth: 0.375 inches Dutside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Detween 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 7.50 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: Na Unit Of Measure: - Demilitarization: No		
Overall Width: Between 4.115 inches and 4.135 inches Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Between 0.300 inches and 0.320 inches Bott Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Nuber synthetic and plastic polyamide Style Designator: No-circular Sheft Life: N/a Uht Of Measure: - Demilitarization: <td>-</td> <td></td>	-	
Between 4.115 inches and 4.135 inches Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Corss-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: No Circular C		
Inside Corner Radius: Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 0.302 inches and 0.322 inches Aperture Length: Between 2.615 inches and 2.635 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Materia! Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Between 0.302 inches and 0.322 inches Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 2.635 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Width: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Na Charter Bitter Bi		
Outside Corner Radius: Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Inside Corner Radius:	
Between 0.302 inches and 0.322 inches Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Between 0.302 inches and 0.322 inches	
Aperture Width: Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outside Corner Radius:	
Between 2.615 inches and 2.635 inches Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.302 inches and 0.322 inches	
Aperture Length: Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Aperture Width:	
Between 6.365 inches and 6.385 inches Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 2.615 inches and 2.635 inches	
Center To Center Distance Between Bolt Holes Along Width: 1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Aperture Length:	
1.687 inches Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 6.365 inches and 6.385 inches	
Center To Center Distance Between Bolt Holes Along Length: 1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Center To Center Distance Between Bolt Holes Along Width:	
1.781 inches Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.687 inches	
Outside Edge To Bolt Hole Center Distance Along Width: 0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Center To Center Distance Between Bolt Holes Along Length:	
0.375 inches Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: 75.0 sho	1.781 inches	
Outside Edge To Bolt Hole Center Distance Along Length: 0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outside Edge To Bolt Hole Center Distance Along Width:	
0.375 inches Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.375 inches	
Cross-sectional Thickness: Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Outside Edge To Bolt Hole Center Distance Along Length:	
Between 0.300 inches and 0.320 inches Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.375 inches	
Bolt Hole Quantity: 12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Cross-sectional Thickness:	
12 Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.300 inches and 0.320 inches	
Hardness Rating: 75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Bolt Hole Quantity:	
75.0 shore durometer a and 85.0 shore durometer a Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No	12	
Material: Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hardness Rating:	
Rubber synthetic and plastic polyamide Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	75.0 shore durometer a and 85.0 shore durometer a	
Style Designator: Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:	
Non-circular Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rubber synthetic and plastic polyamide	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Non-circular	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
-	Fiig:	
	-	