

View Online at <https://aerobasegroup.com/nsn/5330-00-297-6488>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

Between 0.240 inches and 0.260 inches

**Overall Length:**

Between 9.740 inches and 9.760 inches

**Overall Width:**

Between 7.615 inches and 7.635 inches

**Inside Corner Radius:**

0.500 inches

**Outside Corner Radius:**

0.500 inches

**Aperture Width:**

5.625 inches

**Aperture Length:**

7.750 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 3.990 inches and 4.010 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 5.990 inches and 6.010 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 1.802 inches and 1.822 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 1.865 inches and 1.885 inches

**Cross-sectional Thickness:**

Between 0.125 inches and 0.135 inches

**Bolt Hole Quantity:**

8

**Hardness Rating:**

35.0 shore durometer a and 45.0 shore durometer a

**Material:**

Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu

**Material Specification:**

Astm d2000 grade 5bg415 assn standard single material response

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A032a0