NSN 5330-00-297-9705

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-297-9705

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| Between 0.131 inches and 0.141 inches |
| Overall Length: |
| Between 11.610 inches and 11.640 inches |
| Overall Width: |
| Between 7.610 inches and 7.640 inches |
| Inside Corner Radius: |
| Between 0.485 inches and 0.515 inches |
| Outside Corner Radius: |
| Between 1.047 inches and 1.077 inches |
| Aperture Width: |
| 6.501 inches |
| Aperture Length: |
| 10.501 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.875 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.875 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 1.000 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 1.125 inches |
| Cross-sectional Thickness: |
| Between 0.047 inches and 0.077 inches |
| Bolt Hole Quantity: |
| 20 |
| Hardness Rating: |
| 40.0 shore durometer a and 50.0 shore durometer a |
| Material: |
| Rubber chloroprene class cr |
| Material Specification: |
| Mil-g-1149, type 1 military specification single material response |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5330-00-297-9705

Gasket - Page 2 of 2

Fiig: A032a0

Mil-std (military Standard):

Mil-g-1149 spec.

