

View Online at <https://aerobasegroup.com/nsn/5330-00-298-0190>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

Between 0.193 inches and 0.213 inches

Overall Length:

Between 1.375 inches and 1.391 inches

Temperature Rating:

-55.0 degrees celsius and 85.0 degrees celsius

Overall Width:

Between 1.375 inches and 1.391 inches

Aperture Diameter:

Between 1.125 inches and 1.141 inches

Outside Corner Radius:

0.156 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.053 inches and 1.073 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.053 inches and 1.073 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.156 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.156 inches

Cross-sectional Thickness:

Between 0.021 inches and 0.041 inches

Bolt Hole Quantity:

4

Hardness Rating:

55.0 shore durometer a and 65.0 shore durometer a

Maximum Pressure Rating:

30.0 pounds per square inch

Material:

Rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu

Material Specification:

Astm d2000 grade 5bg612-3 assn standard single material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0