## NSN 5330-00-455-6177

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-455-6177

| Cross Sectional Shape:                                     |
|------------------------------------------------------------|
| Solid single or composition                                |
| Hole Diameter:                                             |
| Between 0.146 inches and 0.166 inches                      |
| Overall Length:                                            |
| Between 0.865 inches and 0.885 inches                      |
| Overall Width:                                             |
| Between 0.865 inches and 0.885 inches                      |
| Outside Corner Radius:                                     |
| Between 0.115 inches and 0.135 inches                      |
| Center To Center Distance Between Bolt Holes Along Width:  |
| Between 0.615 inches and 0.635 inches                      |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 0.615 inches and 0.635 inches                      |
| Outside Edge To Bolt Hole Center Distance Along Width:     |
| Between 0.115 inches and 0.135 inches                      |
| Outside Edge To Bolt Hole Center Distance Along Length:    |
| Between 0.115 inches and 0.135 inches                      |
| Cross-sectional Thickness:                                 |
| 0.016 inches                                               |
| Material Specification:                                    |
| Hh-p-96 federal specification all material responses       |
| Shelf Life:                                                |
| N/a                                                        |
| Unit Of Measure:                                           |
|                                                            |
| Demilitarization:                                          |
| No                                                         |
| Fiig:                                                      |
| A032a0                                                     |
|                                                            |