NSN 5330-00-514-4905

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-514-4905

Cross Sectional Shape:
Metal and synthetic rubber
Hole Diameter:
0.406 inches
Overall Length:
5.875 inches
Overall Width:
4.750 inches
Aperture Diameter:
3.047 inches
Outside Corner Radius:
0.375 inches
Center To Center Distance Between Bolt Holes Along Width:
4.000 inches
Center To Center Distance Between Bolt Holes Along Length:
5.125 inches
Outside Edge To Bolt Hole Center Distance Along Width:
0.375 inches
Outside Edge To Bolt Hole Center Distance Along Length:
0.375 inches
Cross-sectional Thickness:
Cross-sectional Thickness: 0.016 inches
0.016 inches
0.016 inches Bolt Hole Quantity:
0.016 inches Bolt Hole Quantity: 4
0.016 inches Bolt Hole Quantity: 4 Material:
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification:
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator:
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data:
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data: Engine, gasoline, reciprocating
0.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data: Engine, gasoline, reciprocating Shelf Life:
D.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data: Engine, gasoline, reciprocating Shelf Life: N/a
D.016 inches Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data: Engine, gasoline, reciprocating Shelf Life: N/a
Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data: Engine, gasoline, reciprocating Shelf Life: N/a Unit Of Measure:
Bolt Hole Quantity: 4 Material: Aluminum alloy 5056 and rubber chloroprene class cr Material Specification: Ams4182 assn standard 1st material response and ams3222 assn standard 2nd material response Style Designator: Non-circular Fsc Application Data: Engine, gasoline, reciprocating Shelf Life: N/a Unit Of Measure: Demilitarization: