

View Online at <https://aerobasegroup.com/nsn/5330-00-514-7372>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

Between 0.243 inches and 0.253 inches

**Overall Length:**

Between 8.720 inches and 8.780 inches

**Overall Width:**

Between 5.970 inches and 6.030 inches

**Inside Corner Radius:**

Between 0.090 inches and 0.150 inches

**Aperture Width:**

Between 4.910 inches and 5.090 inches

**Aperture Length:**

Between 7.660 inches and 7.840 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.750 inches

**Center To Center Distance Between Bolt Holes Along Length:**

2.750 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.220 inches and 0.280 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.220 inches and 0.280 inches

**Cross-sectional Thickness:**

Between 0.470 inches and 0.770 inches

**Bolt Hole Quantity:**

10

**Hardness Rating:**

35.0 shore durometer a and 55.0 shore durometer a

**Material:**

Rubber chloroprene class cr or rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu

**Material Specification:**

Mil-g-1149, type 1, cl 1 military specification 1st material response or astm d2000 2bg415 assn standard 2nd material response or astm d2000 2bg415 assn standard 3rd material response or astm d2000 2bg415 assn standard 4th material response

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A032a0

**Mil-std (military Standard):**

Mil-g-1149 spec.