

View Online at <https://aerobasegroup.com/nsn/5330-00-514-7372>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

Between 0.243 inches and 0.253 inches

Overall Length:

Between 8.720 inches and 8.780 inches

Overall Width:

Between 5.970 inches and 6.030 inches

Inside Corner Radius:

Between 0.090 inches and 0.150 inches

Aperture Width:

Between 4.910 inches and 5.090 inches

Aperture Length:

Between 7.660 inches and 7.840 inches

Center To Center Distance Between Bolt Holes Along Width:

2.750 inches

Center To Center Distance Between Bolt Holes Along Length:

2.750 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.220 inches and 0.280 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.220 inches and 0.280 inches

Cross-sectional Thickness:

Between 0.470 inches and 0.770 inches

Bolt Hole Quantity:

10

Hardness Rating:

35.0 shore durometer a and 55.0 shore durometer a

Material:

Rubber chloroprene class cr or rubber butadiene-acrylonitrile class nbr or rubber polyester urethane class au or rubber polyether urethane class eu

Material Specification:

Mil-g-1149, type 1, cl 1 military specification 1st material response or astm d2000 2bg415 assn standard 2nd material response or astm d2000 2bg415 assn standard 3rd material response or astm d2000 2bg415 assn standard 4th material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0

Mil-std (military Standard):

Mil-g-1149 spec.