

View Online at <https://aerobasegroup.com/nsn/5330-00-515-3965>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

Between 0.210 inches and 0.250 inches

Overall Length:

Between 7.920 inches and 7.960 inches

Overall Width:

Between 3.360 inches and 3.400 inches

Inside Corner Radius:

Between 0.220 inches and 0.280 inches

Outside Corner Radius:

Between 0.220 inches and 0.280 inches

Aperture Width:

Between 1.970 inches and 2.030 inches

Aperture Length:

Between 6.530 inches and 6.590 inches

Center To Center Distance Between Bolt Holes Along Width:

1.500 inches

Center To Center Distance Between Bolt Holes Along Length:

1.500 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.930 inches and 0.950 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.836 inches and 0.886 inches

Cross-sectional Thickness:

Between 0.120 inches and 0.140 inches

Bolt Hole Quantity:

12

Hardness Rating:

65.0 shore durometer a and 75.0 shore durometer a

Material:

Rubber synthetic

Style Designator:

Non-circular

Test Data Document:

91499-jcn20a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Turbine, refrigeration unit, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0