NSN 5330-00-542-0682

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-542-0682

| Cross Sectional Shape: |
|---|
| Solid single or composition |
| Hole Diameter: |
| 0.196 inches |
| Overall Length: |
| 3.000 inches |
| Overall Width: |
| 1.188 inches |
| Outside Corner Radius: |
| 0.172 inches |
| Aperture Width: |
| 0.938 inches |
| Aperture Length: |
| 2.250 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 0.844 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 2.656 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.172 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.172 inches |
| Cross-sectional Thickness: |
| 0.062 inches |
| Bolt Hole Quantity: |
| 4 |
| Hardness Rating: |
| 40.0 shore durometer a |
| Material: |
| Rubber chloroprene class cr |
| Material Specification: |
| Mil-s-6855, cl 2, gr 40 military specification single material response |
| Style Designator: |
| Non-circular |
| Reference Number Differentiating Characteristics: |
| As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No No |

NSN 5330-00-542-0682

Gasket - Page 2 of 2



Fiig:

A032a0

Mil-std (military Standard):

Mil-s-6855 spec.