NSN 5330-00-560-5627

Preformed Packing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-560-5627

Cross Secti	onal Shape:
O-ring	
Tempuratur	e Rating:
-65.0 degree	es fahrenheit and 160.0 degrees fahrenheit
Cross Secti	on Outside Diameter:
Between 0.1	35 inches and 0.143 inches
Cross-secti	onal Height:
Between 0.1	35 inches and 0.143 inches
Center Hole	Diameter:
Between 2.2	24 inches and 2.244 inches
Peripheral [Diameter:
Between 2.4	84 inches and 2.540 inches
Elongation	Percentage:
164	
Hardness R	ating:
70.0 shore d	lurometer a and 80.0 shore durometer a
Criticality C	ode Justification:
Abjh and sup	qq
Operating M	fedium:
Hydraulic flu	id
Functional	Description:
Hydraulic flu	id mil-h-5606, shock absorber struts, actuating cylinders and valves
Color:	
Red	
Material:	
Rubber buta	diene-acrylonitrile class nbr
Material Spo	ecification:
Mil-p-5516, d	class a /inactive/ military specification single material response
Reference D	Data And Literature:
Tm9-1440-1	250-24p-1-1/-2
Relationshi	p To Similar Equipment:
Similar to ns	n 5330-00-194-3713 p/n an6230-6 except packaging
Supplement	tary Features:
W/ special u	nit package in accordance w/ packaging data sheet-engineering records-shelf life 48 months
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	ition:
No	
Fiig:	
A032a0	

NSN 5330-00-560-5627

Preformed Packing - Page 2 of 2

Mil-std (military Standard):

Mil-p-5516 spec.

