## NSN 5330-00-560-5627

Preformed Packing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-560-5627
Cross Sectional Shape:
O-ring
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit
Cross Section Outside Diameter:
Between 0.135 inches and 0.143 inches
Cross-sectional Height:
Between 0.135 inches and 0.143 inches
Center Hole Diameter:
Between 2.224 inches and 2.244 inches
Peripheral Diameter:
Between 2.484 inches and 2.540 inches
Elongation Percentage:
164
Hardness Rating:
70.0 shore durometer a and 80.0 shore durometer a
Criticality Code Justification:
Abjh and supp
Operating Medium:
Hydraulic fluid
Functional Description:
Hydraulic fluid mil-h-5606, shock absorber struts, actuating cylinders and valves
Color:
Red
Material:
Rubber butadiene-acrylonitrile class nbr
Material Specification:
Mil-p-5516, class a /inactive/ military specification single material response
Reference Data And Literature:
Tm9-1440-1250-24p-1-1/-2
Relationship To Similar Equipment:
Similar to nsn 5330-00-194-3713 p/n an6230-6 except packaging
Supplementary Features:
W/ special unit package in accordance w/ packaging data sheet-engineering records-shelf life 48 months
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A032a0

## NSN 5330-00-560-5627

Preformed Packing - Page 2 of 2



Mil-std (military Standard):

Mil-p-5516 spec.