NSN 5330-00-576-9783

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-576-9783

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| 0.290 inches |
| Overall Length: |
| 4.000 inches |
| Overall Width: |
| 3.380 inches |
| Inside Corner Radius: |
| 0.380 inches |
| Outside Corner Radius: |
| 0.380 inches |
| Aperture Width: |
| 2.140 inches |
| Aperture Length: |
| 2.760 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 2.500 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 3.120 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.440 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.440 inches |
| Cross-sectional Thickness: |
| 0.031 inches |
| Bolt Hole Quantity: |
| 4 |
| Elongation Percentage: |
| 300 |
| Hardness Rating: |
| 35.0 shore durometer a and 55.0 shore durometer a |
| Material: |
| Rubber butadiene-acrylonitrile class nbr |
| Material Specification: |
| Mil-r-2765 military specification single material response |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5330-00-576-9783

Gasket - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-2765 spec.