NSN 5330-00-580-9023

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-580-9023

Cross Sectional Shape:
Solid single or composition
Hole Diameter:
Between 0.360 inches and 0.390 inches
Overall Length:
Between 2.885 inches and 2.915 inches
Overall Width:
Between 2.885 inches and 2.915 inches
Aperture Diameter:
Between 2.065 inches and 2.095 inches
Outside Corner Radius:
Between 0.285 inches and 0.315 inches
Center To Center Distance Between Bolt Holes Along Width:
Between 1.990 inches and 2.010 inches
Center To Center Distance Between Bolt Holes Along Length:
Between 1.990 inches and 2.010 inches
Outside Edge To Bolt Hole Center Distance Along Width:
Cutside Luge To Boit Hole Center Distance Along Width.
Between 0.435 inches and 0.465 inches
Between 0.435 inches and 0.465 inches
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length:
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness:
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material:
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic Shelf Life:
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic Shelf Life: N/a
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic Shelf Life: N/a
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic Shelf Life: N/a Unit Of Measure:
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic Shelf Life: N/a Unit Of Measure: Demilitarization:
Between 0.435 inches and 0.465 inches Outside Edge To Bolt Hole Center Distance Along Length: Between 0.435 inches and 0.465 inches Cross-sectional Thickness: Between 0.006 inches and 0.007 inches Material: Cellulose and rubber synthetic Shelf Life: N/a Unit Of Measure: Demilitarization: No