## NSN 5330-00-592-9128

Spiral Wound Gasket - Page 1 of 1

Mil-s-5059 spec.



View Online at https://aerobasegroup.com/nsn/5330-00-592-9128

Cross Sectional Shape:
Metal winding w/ soft filler
Hole Diameter:
Between 0.195 inches and 0.210 inches
Tempurature Rating:
-80.0 degrees fahrenheit and 375.0 degrees fahrenheit
Bolt Circle Diameter:
1.500 inches
Overall Width:
1.856 inches
Aperture Diameter:
0.904 inches
Outside Corner Radius:
0.219 inches
Side Radius From Gasket Center:
0.875 inches
Cross-sectional Thickness:
Between 0.084 inches and 0.100 inches
Gage Ring Thickness:
0.094 inches
Bolt Hole Quantity:
4
Hardness Rating:
65.0 shore durometer a and 75.0 shore durometer a
Material:
Rubber silicone class q and steel comp 302 or rubber silicone class q and steel comp 302
Material Specification:
S604-70, fscm 83259 mfr ref 1st material response and mil-s-5059 military specification 1st material response or zz-r-765, cl 2b, gr 70
federal specification 2nd material response and mil-s-5059 military specification 2nd material response
Style Designator:
Non-circular Section 1. The section
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A032a0
Mil-std (military Standard):