NSN 5330-00-593-9515

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-593-9515

Cross	Se	ction	nal	Sha	ne:
UI U33	OC.	CLICI	ıaı	ulia	vc.

Solid single or composition

Hole Diameter:

Between 0.246 inches and 0.260 inches

Overall Length:

Between 2.844 inches and 2.906 inches

Overall Width:

Between 2.844 inches and 2.906 inches

Inside Corner Radius:

Between 0.094 inches and 0.156 inches

Aperture Width:

Between 0.719 inches and 0.781 inches

Aperture Length:

Between 1.094 inches and 1.156 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.094 inches and 1.156 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.094 inches and 1.156 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.281 inches and 0.343 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.281 inches and 0.343 inches

Cross-sectional Thickness:

Between 0.022 inches and 0.042 inches

Bolt Hole Quantity:

8

Material:

Asbestos and rubber natural or rubber synthetic

Material Specification:

Mil-a-7021, cl 1 military specification all material responses

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-a-7021 spec.