## NSN 5330-00-634-8287

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-634-8287

Solid single or composition  Hole Diameter:  0.280 inches  Bolt Circle Diameter:  1.660 inches  Overall Width:  2.220 inches  Aperture Diameter:  0.780 inches  Outside Corner Radius:  0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
0.280 inches  Bolt Circle Diameter:  1.660 inches  Overall Width:  2.220 inches  Aperture Diameter:  0.780 inches  Outside Corner Radius:  0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
Bolt Circle Diameter:  1.660 inches  Overall Width:  2.220 inches  Aperture Diameter:  0.780 inches  Outside Corner Radius:  0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
1.660 inches  Overall Width: 2.220 inches  Aperture Diameter: 0.780 inches  Outside Corner Radius: 0.280 inches  Side Radius From Bolt Circle: 1.940 inches  Cross-sectional Thickness: 0.031 inches  Bolt Hole Quantity: 2  Material: Asbestos and rubber synthetic  Material Specification:
Overall Width:  2.220 inches  Aperture Diameter:  0.780 inches  Outside Corner Radius:  0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
2.220 inches  Aperture Diameter: 0.780 inches  Outside Corner Radius: 0.280 inches  Side Radius From Bolt Circle: 1.940 inches  Cross-sectional Thickness: 0.031 inches  Bolt Hole Quantity: 2  Material: Asbestos and rubber synthetic  Material Specification:
Aperture Diameter:  0.780 inches  Outside Corner Radius:  0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
0.780 inches  Outside Corner Radius: 0.280 inches  Side Radius From Bolt Circle: 1.940 inches  Cross-sectional Thickness: 0.031 inches  Bolt Hole Quantity: 2  Material: Asbestos and rubber synthetic  Material Specification:
Outside Corner Radius:  0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
0.280 inches  Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
Side Radius From Bolt Circle:  1.940 inches  Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
1.940 inches  Cross-sectional Thickness: 0.031 inches  Bolt Hole Quantity: 2  Material: Asbestos and rubber synthetic  Material Specification:
Cross-sectional Thickness:  0.031 inches  Bolt Hole Quantity:  2  Material:  Asbestos and rubber synthetic  Material Specification:
0.031 inches  Bolt Hole Quantity: 2  Material: Asbestos and rubber synthetic  Material Specification:
Bolt Hole Quantity:  2  Material: Asbestos and rubber synthetic  Material Specification:
2  Material: Asbestos and rubber synthetic  Material Specification:
Material: Asbestos and rubber synthetic Material Specification:
Asbestos and rubber synthetic  Material Specification:
Material Specification:
Ams 3232 assn standard single material response
Style Designator:
Non-circular
Fsc Application Data:
Engine, aircraft, reciprocating
Shelf Life:
Shelf Life: N/a
N/a
N/a
N/a Unit Of Measure:
N/a Unit Of Measure: Demilitarization: