

View Online at <https://aerobasegroup.com/nsn/5330-00-640-8538>

Cross Sectional Shape:

Outside grooved, straight face

Inside Diameter:

2.000 inches

Outside Diameter:

2.282 inches

Material Thickness:

0.125 inches

Ring Style:

Concentric

Outer Edge Thickness:

0.094 inches

Joint Style:

Diagonal joint

End Application:

W/s: forrestal class cv; fire control system, missile mk 74 (fcs); virginia class cgn (4a); kidd class ddg; aircraft, hercules c-130f; aircraft, hercules kc-130; elevators, cargo/weapons; aircraft, awacs, e-3a; tank, combat, ft, 120mm gun (m1a1); aircraft (ac-130h, mc-130h, ec-130e, hc-130); nimitz class cvn; fms-build frigates class ships; deck machinery; aircraft, stratolifter c-135

Material:

Any acceptable

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Test Data Document:

81349-mil-s-5049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms28776 government standard

Fsc Application Data:

Hydraulic system, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A08400

Mil-std (military Standard):

Mil-s-5049 spec.