

View Online at <https://aerobasegroup.com/nsn/5330-00-640-8538>

**Cross Sectional Shape:**

Outside grooved, straight face

**Inside Diameter:**

2.000 inches

**Outside Diameter:**

2.282 inches

**Material Thickness:**

0.125 inches

**Ring Style:**

Concentric

**Outer Edge Thickness:**

0.094 inches

**Joint Style:**

Diagonal joint

**End Application:**

W/s: forrestal class cv; fire control system, missile mk 74 (fcs); virginia class cgn (4a); kidd class ddg; aircraft, hercules c-130f; aircraft, hercules kc-130; elevators, cargo/weapons; aircraft, awacs, e-3a; tank, combat, ft, 120mm gun (m1a1); aircraft (ac-130h, mc-130h, ec-130e, hc-130); nimitz class cvn; fms-build frigates class ships; deck machinery; aircraft, stratolifter c-135

**Material:**

Any acceptable

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Test Data Document:**

81349-mil-s-5049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

96906-ms28776 government standard

**Fsc Application Data:**

Hydraulic system, acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A08400

**Mil-std (military Standard):**

Mil-s-5049 spec.