

View Online at <https://aerobasegroup.com/nsn/5330-00-738-2459>

Cross Sectional Shape:

Metal and synthetic rubber

Hole Diameter:

0.266 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit

Bolt Circle Diameter:

1.855 inches

Aperture Diameter:

0.904 inches

Outside Corner Radius:

0.220 inches

Cross-sectional Thickness:

0.121 inches

Gage Ring Thickness:

0.081 inches

Hardness Rating:

65.0 shore durometer a and 75.0 shore durometer a

Material:

Aluminum alloy 5052 and rubber butadiene-acrylonitrile class nbr or aluminum alloy 5052 and rubber polyester urethane class au or aluminum alloy 5052 and rubber polyether urethane class eu

Material Specification:

Qq-a-250/8, alloy 5052 federal specification 1st material response and astm d2000 5bg715 assn standard 2nd material response or qq-a-250/8 alloy 5052 federal specification 3rd material response and astm d2000 5bg715 assn standard 4th material response or qq-a-250/8 alloy 5052 federal specification 5th material response and astm d2000 5bg715 assn standard 6th material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0

Mil-std (military Standard):

Mil-a-8625 spec.