

View Online at <https://aerobasegroup.com/nsn/5330-00-738-2459>

**Cross Sectional Shape:**

Metal and synthetic rubber

**Hole Diameter:**

0.266 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Bolt Circle Diameter:**

1.855 inches

**Aperture Diameter:**

0.904 inches

**Outside Corner Radius:**

0.220 inches

**Cross-sectional Thickness:**

0.121 inches

**Gage Ring Thickness:**

0.081 inches

**Hardness Rating:**

65.0 shore durometer a and 75.0 shore durometer a

**Material:**

Aluminum alloy 5052 and rubber butadiene-acrylonitrile class nbr or aluminum alloy 5052 and rubber polyester urethane class au or aluminum alloy 5052 and rubber polyether urethane class eu

**Material Specification:**

Qq-a-250/8, alloy 5052 federal specification 1st material response and astm d2000 5bg715 assn standard 2nd material response or qq-a-250/8 alloy 5052 federal specification 3rd material response and astm d2000 5bg715 assn standard 4th material response or qq-a-250/8 alloy 5052 federal specification 5th material response and astm d2000 5bg715 assn standard 6th material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 type 2 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-a-8625 spec.