

View Online at <https://aerobasegroup.com/nsn/5330-00-805-7704>

**Cross Sectional Shape:**

Metal and synthetic rubber

**Hole Diameter:**

Between 0.261 inches and 0.276 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Bolt Circle Diameter:**

Between 2.337 inches and 2.347 inches

**Overall Width:**

Between 2.869 inches and 2.879 inches

**Aperture Diameter:**

Between 1.133 inches and 1.143 inches

**Outside Corner Radius:**

Between 0.250 inches and 0.282 inches

**Outside Corner Inverted Radius:**

Between 0.250 inches and 0.282 inches

**Side Radius From Gasket Center:**

Between 0.905 inches and 0.937 inches

**Cross-sectional Thickness:**

0.120 inches

**Gage Ring Thickness:**

Between 0.076 inches and 0.084 inches

**Bolt Hole Quantity:**

4

**Elongation Percentage:**

250

**Hardness Rating:**

70.0 shore durometer a

**Material:**

Rubber butadiene-acrylonitrile class nbr

**Material Specification:**

Mil-r-7362 comp a type 2 military specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, tya military specification single treatment response

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A032a0

**Mil-std (military Standard):**

Mil-r-7362 spec.