

View Online at <https://aerobasegroup.com/nsn/5330-00-805-7704>

Cross Sectional Shape:

Metal and synthetic rubber

Hole Diameter:

Between 0.261 inches and 0.276 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit

Bolt Circle Diameter:

Between 2.337 inches and 2.347 inches

Overall Width:

Between 2.869 inches and 2.879 inches

Aperture Diameter:

Between 1.133 inches and 1.143 inches

Outside Corner Radius:

Between 0.250 inches and 0.282 inches

Outside Corner Inverted Radius:

Between 0.250 inches and 0.282 inches

Side Radius From Gasket Center:

Between 0.905 inches and 0.937 inches

Cross-sectional Thickness:

0.120 inches

Gage Ring Thickness:

Between 0.076 inches and 0.084 inches

Bolt Hole Quantity:

4

Elongation Percentage:

250

Hardness Rating:

70.0 shore durometer a

Material:

Rubber butadiene-acrylonitrile class nbr

Material Specification:

Mil-r-7362 comp a type 2 military specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, tya military specification single treatment response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0

Mil-std (military Standard):

Mil-r-7362 spec.