NSN 5330-00-807-2979

Gasket - Page 1 of 1

A032a0



View Online at https://aerobasegroup.com/nsn/5330-00-807-2979

| Cross Sectional Shape: |
|---|
| Solid single or composition |
| Hole Diameter: |
| Between 0.266 inches and 0.297 inches |
| |
| Overall Length: 16.250 inches |
| Overall Width: |
| 7.000 inches |
| |
| Aperture Width: |
| 5.500 inches |
| Aperture Length: |
| 14.750 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| Between 3.109 inches and 3.141 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 3.859 inches and 3.891 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.375 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.375 inches |
| Cross-sectional Thickness: |
| Between 0.109 inches and 0.141 inches |
| Bolt Hole Quantity: |
| 12 |
| Hardness Rating: |
| 35.0 shore durometer a and 45.0 shore durometer a |
| Material: |
| Rubber polyisoprene natural class nr or rubber butadiene-styrene class sbr or rubber isobutylene-isoprene class iir or rubber |
| ethylene-propylene-diene class epdm or rubber polyisoprene synthetic class ir |
| Material Specification: |
| Astm d2000 gr 4aa420 assn standard single material response |
| Style Designator: |
| Non-circular Section 1. The section |
| Fsc Application Data: |
| Radar set guided missile battery control central |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |