NSN 5330-00-836-4355

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-00-836-4355

Cross	Se	ction	nal	Sha	ne:
UI U33	OC.	CLICI	ıaı	ulia	vc.

Solid single or composition

Hole Diameter:

Between 0.193 inches and 0.213 inches

Overall Length:

Between 1.500 inches and 1.516 inches

Overall Width:

Between 1.500 inches and 1.516 inches

Aperture Diameter:

Between 1.250 inches and 1.266 inches

Outside Corner Radius:

Between 0.162 inches and 0.182 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.146 inches and 1.166 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.146 inches and 1.166 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.172 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.172 inches

Cross-sectional Thickness:

Between 0.026 inches and 0.036 inches

Bolt Hole Quantity:

•

End Application:

Mrap rg-33

Hardness Rating:

45.0 shore durometer a and 55.0 shore durometer a

Special Features:

Fungus resistant.

Material:

Rubber chloroprene class cr

Material Specification:

Astm d2000 2bc515abc1f2z assn standard single material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5330-00-836-4355

Gasket - Page 2 of 2



Fiig:

A032a0