## NSN 5330-00-837-2352

Gasket - Page 1 of 1



2

| View Online at https://aerobasegroup.com/nsn/5330-00-837-2352      |
|--|
| Cross Sectional Shape:   |
| Solid single or composition  |
| Hole Diameter:   |
| Between 0.208 inches and 0.215 inches                              |
| Overall Length:  |
| Between 2.860 inches and 2.900 inches                              |
| Overall Width:   |
| Between 2.860 inches and 2.900 inches                              |
| Aperture Diameter:   |
| Between 1.850 inches and 1.900 inches                              |
| Outside Corner Radius:   |
| Between 0.790 inches and 0.830 inches                              |
| Center To Center Distance Between Bolt Holes Along Width:          |
| 2.032 inches   |
| Center To Center Distance Between Bolt Holes Along Length:         |
| 2.032 inches   |
| Outside Edge To Bolt Hole Center Distance Along Width:             |
| 0.414 inches   |
| Outside Edge To Bolt Hole Center Distance Along Length:            |
| 0.414 inches   |
| Cross-sectional Thickness:   |
| 0.062 inches   |
| Bolt Hole Quantity:  |
| 4  |
| Hardness Rating:   |
| 47.0 shore durometer a and 56.0 shore durometer a                  |
| Material:  |
| Rubber chloroprene class cr  |
| Material Specification:  |
| Mil-r-1149, type 1 military specification single material response |
| Style Designator:  |
| Non-circular   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A032a0   |

Mil-r-1149 spec.

Mil-std (military Standard):