NSN 5330-00-837-2352

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-837-2352

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| Between 0.208 inches and 0.215 inches |
| Overall Length: |
| Between 2.860 inches and 2.900 inches |
| Overall Width: |
| Between 2.860 inches and 2.900 inches |
| Aperture Diameter: |
| Between 1.850 inches and 1.900 inches |
| Outside Corner Radius: |
| Between 0.790 inches and 0.830 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 2.032 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 2.032 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.414 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.414 inches |
| Cross-sectional Thickness: |
| 0.062 inches |
| Bolt Hole Quantity: |
| 4 |
| Hardness Rating: |
| 47.0 shore durometer a and 56.0 shore durometer a |
| Material: |
| Rubber chloroprene class cr |
| Material Specification: |
| Mil-r-1149, type 1 military specification single material response |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Νο |
| Fiig: |
| A032a0 |
| Mil-std (military Standard): |
| Mil-r-1149 spec. |
| |