

View Online at <https://aerobasegroup.com/nsn/5330-00-839-1273>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

Between 0.152 inches and 0.159 inches

Overall Length:

Between 2.350 inches and 2.370 inches

Overall Width:

Between 1.990 inches and 2.010 inches

Inside Corner Radius:

Between 0.110 inches and 0.130 inches

Outside Corner Radius:

Between 0.110 inches and 0.130 inches

Aperture Width:

Between 1.490 inches and 1.510 inches

Aperture Length:

Between 1.490 inches and 1.510 inches

Center To Center Distance Between Bolt Holes Along Width:

1.624 inches

Center To Center Distance Between Bolt Holes Along Length:

2.000 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.170 inches and 0.210 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.160 inches and 0.200 inches

Cross-sectional Thickness:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Hardness Rating:

45.0 shore durometer a and 53.0 shore durometer a

Maximum Pressure Rating:

95.0 pounds per square inch

Material:

Rubber butadiene-styrene class sbr and rubber chloroprene class cr

Material Specification:

Mil-g-900 type 1 cl1 military specification 1st material response and mil-g-1149 type 1 cl 2 military specification 2nd material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0

Mil-std (military Standard):

Mil-g-900 spec.