

View Online at <https://aerobasegroup.com/nsn/5330-00-902-7950>

**Cross Sectional Shape:**

Metal and synthetic rubber

**Hole Diameter:**

Between 0.323 inches and 0.338 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Bolt Circle Diameter:**

Between 3.354 inches and 3.364 inches

**Overall Width:**

Between 3.979 inches and 3.989 inches

**Aperture Diameter:**

Between 1.836 inches and 1.846 inches

**Outside Corner Radius:**

Between 0.296 inches and 0.328 inches

**Outside Corner Inverted Radius:**

Between 0.296 inches and 0.328 inches

**Side Radius From Gasket Center:**

Between 1.359 inches and 1.391 inches

**Cross-sectional Thickness:**

0.120 inches

**Gage Ring Thickness:**

Between 0.076 inches and 0.084 inches

**Bolt Hole Quantity:**

4

**Elongation Percentage:**

200

**Hardness Rating:**

65.0 shore durometer a

**Material:**

Aluminum alloy 6061 and rubber butadiene-acrylonitrile class nbr

**Material Specification:**

Qq-a-250/11, t6 federal specification 1st material response and mil-p-5315 military specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-p-5315 spec.