NSN 5330-00-921-0490

Rubber Strip - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-921-0490

Cross Sectional Shape: Rectangular Fabrication Method: Solid Nonmetallic Hardness Rating: 35.0 shore durometer a and 55.0 shore durometer a
Fabrication Method: Solid Nonmetallic Hardness Rating: 35.0 shore durometer a and 55.0 shore durometer a
Solid Nonmetallic Hardness Rating: 35.0 shore durometer a and 55.0 shore durometer a
Nonmetallic Hardness Rating: 35.0 shore durometer a and 55.0 shore durometer a
35.0 shore durometer a and 55.0 shore durometer a
AN T - 1 - 0 - 0 - 1 - 1 - 1
Min. Tensile Strength (psi):
1500 pounds per square inch
Tempurature Rating:
Not rated
Length:
Between 49.625 inches and 49.875 inches
Surface Condition:
Smooth
Cross-sectional Height:
1.000 inches
Cross-sectional Width:
0.125 inches
Color:
Black
Material:
Rubber, synthetic, mil-std-417, type s, grade sc415a1b1c1f1gz and rubber, synthetic, mil-std-417, type s, grade sc515a1b1c1f1gz
Material:
Rubber chloroprene class cr and rubber chloroprene class cr
Material Specification:
Mil-std-417, type s, grade sc415a1b1c1f1gz military specification 1st material response and mil-std-417, type s, grade sc515a1b1c1f1g
military specification 2nd material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A26800
Mil-std (military Standard):
Mil-std-417 spec.