NSN 5330-00-926-9337

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-926-9337

Cross	Se	ction	nal	Sha	ne:
UI U33	OC.	CLICI	ıaı	ulia	vc.

Solid single or composition

Hole Diameter:

Between 0.209 inches and 0.229 inches

Overall Length:

Between 2.500 inches and 2.516 inches

Overall Width:

Between 2.500 inches and 2.516 inches

Aperture Diameter:

Between 2.188 inches and 2.204 inches

Outside Corner Radius:

Between 0.271 inches and 0.291 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.928 inches and 1.948 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.928 inches and 1.948 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.271 inches and 0.291 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.271 inches and 0.291 inches

Cross-sectional Thickness:

Between 0.026 inches and 0.036 inches

Bolt Hole Quantity:

4

Hardness Rating:

75.0 shore durometer a and 85.0 shore durometer a

Material:

Rubber chloroprene class cr

Material Specification:

Astm d2000 2bc815c1e3 assn standard single material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A032a0