## NSN 5330-00-931-0208

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-931-0208

Cross	Se	ction	nal	Sha	ne:
<b>UI U33</b>	OC.	CLICI	ıaı	ulia	vc.

Metal and synthetic rubber

**Hole Diameter:** 

Between 0.162 inches and 0.182 inches

**Overall Length:** 

Between 1.281 inches and 1.297 inches

**Tempurature Rating:** 

-40.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Overall Width:** 

Between 1.281 inches and 1.297 inches

**Aperture Diameter:** 

Between 1.000 inches and 1.016 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.959 inches and 0.979 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.959 inches and 0.979 inches

**Outside Edge To Bolt Hole Center Distance Along Width:** 

Between 0.151 inches and 0.161 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.151 inches and 0.161 inches

**Cross-sectional Thickness:** 

Between 0.016 inches and 0.024 inches

Material:

Aluminum and rubber chloroprene class cr

**Material Specification:** 

Ams 3222 assn standard 2nd material response

**Fsc Application Data:** 

Electrical connector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A032a0