## NSN 5330-00-932-3671

Gasket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5330-00-932-3671   |
|---|
| Cross Sectional Shape:  |
| Metal and synthetic rubber  |
| Hole Diameter:  |
| Between 0.261 inches and 0.276 inches   |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit   |
| Bolt Circle Diameter:   |
| Between 2.337 inches and 2.347 inches   |
| Overall Width:  |
| 2.874 inches  |
| Aperture Diameter:  |
| Between 1.133 inches and 1.143 inches   |
| Outside Corner Radius:  |
| Between 0.250 inches and 0.281 inches   |
| Outside Corner Inverted Radius:   |
| Between 0.250 inches and 0.281 inches   |
| Side Radius From Gasket Center:   |
| Between 1.166 inches and 1.176 inches   |
| Gage Thickness:   |
| Between 0.076 inches and 0.084 inches   |
| Bolt Hole Quantity:   |
| 4   |
| Elongation Percentage:  |
| 200   |
| Hardness Rating:  |
| 60.0 shore durometer a and 70.0 shore durometer a   |
| Material:   |
| Aluminum alloy 6061 and rubber butadiene-acrylonitrile class nbr  |
| Material Specification:   |
| Qq-a-250/11 federal specification 1st material response and mil-p-5315 military specification 2nd material response |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, type 2 military specification single treatment response   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

Fiig:

A032a0

## NSN 5330-00-932-3671

Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-p-5315 spec.