NSN 5330-00-944-5940

Gasket - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5550-00-944-5940 |
|---|
| Cross Sectional Shape: |
| Metal and synthetic rubber |
| Hole Diameter: |
| Between 0.200 inches and 0.215 inches |
| Tempurature Rating: |
| -20.0 degrees fahrenheit and 400.0 degrees fahrenheit |
| Bolt Circle Diameter: |
| Between 1.630 inches and 1.640 inches |
| Overall Width: |
| 2.073 inches |
| Aperture Diameter: |
| Between 0.664 inches and 0.674 inches |
| Outside Corner Radius: |
| Between 0.203 inches and 0.234 inches |
| Outside Corner Inverted Radius: |
| Between 0.203 inches and 0.234 inches |
| Side Radius From Gasket Center: |
| Between 0.620 inches and 0.630 inches |
| Cross-sectional Thickness: |
| 0.132 inches |
| Gage Ring Thickness: |
| Between 0.084 inches and 0.100 inches |
| Bolt Hole Quantity: |
| 4 |
| Elongation Percentage: |
| 125 |
| Hardness Rating: |
| 75.0 shore durometer a |
| Material: |
| Steel comp 302 and rubber fluorocarbon class fpm |
| Material Specification: |
| Mil-s-5059 military specification 1st material response and mil-r-83248 type 2, cl 1 military specification 2nd material response |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A032a0

NSN 5330-00-944-5940

Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-s-5059 spec.