

View Online at <https://aerobasegroup.com/nsn/5330-00-953-2432>

**General Description:**

Brass, qq-b-626 composition 11, soft temper, 0.467 in. Min, 0.477 in. Max o/a lg, 1.2591 in. Min, 1.2597 in. Maximum largest od, 0.102 in. Min, 0.124 in. Maximum lg largest od, 1.137 in. Min, 1.139 in. Maximum od 1st end, 0.084 in. Min, 0.104 in. Maximum lg 1st end, 1.097 in. Min, 1.098 in. Maximum od 2nd end 1st step, 0.047 in. Min, 0.077 in. Maximum lg 2nd end 1st step, 0.990 in. Min, 1.010 in. Maximum od 2nd end 2nd step, 0.192 in. Min, 0.214 in. Maximum lg 2nd end 2nd step, 29 degrees 30 minutes min, 30 degrees 30 minutes maximum by 0.990 in. Min, 1.010 in. Maximum diameter chamfer 1st end, v-groove located on od 2nd end 1st step, 29 deg 30 minutes min, 30 degrees 30 minutes maximum groove wall angle, 0.016 in. Max radius groove bottom, 0.005 in. Min, 0.010 in. Maximum lg from edges of shoulders to groove edges, 0.865 in. Min, 0.885 in. Maximum id, id on 1st end tapered 15 degrees 30 minutes min, 16 degrees 30 minutes maximum from 0.990 in. Min, 1.010 in. Maximum diameter by 0.208 in. Min, 0.228 in. Maximum deep, 2 shoulders located on id, 0.208 in. Min, 0.228 in. Maximum lg from 1st end to 1st shoulder face, 0.386 in

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No