

View Online at <https://aerobasegroup.com/nsn/5330-00-975-7033>

Hole Diameter:

0.438 inches

Overall Length:

6.375 inches

Overall Width:

5.875 inches

Inside Corner Radius:

0.250 inches

Outside Corner Radius:

0.375 inches

Aperture Width:

4.250 inches

Aperture Length:

4.750 inches

Center To Center Distance Between Bolt Holes Along Width:

5.125 inches

Center To Center Distance Between Bolt Holes Along Length:

5.625 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.375 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.375 inches

Cross-sectional Thickness:

0.031 inches

Bolt Hole Quantity:

4

Special Features:

One cut-away positioned on the gasket width, pivot of radius 3.531 in. From lower right bolt hole center and 0.562 in. Inward from bolt hole center line along width, cut-away encribes a 0.500 in. Circle radius width inverted corner radii of 0.250 in.; one punch hole with hole center positioned 1.234 in. Above lower right bolthole and 0.375 in. Inward from bolt center line along width, punch hole dia. Is 0.266 in. Aperture forms a frame around punch hole, frame having a 0.250 in. Radius from punch hole center and inverted corner radii of 0.250 in.

Material:

Rubber and asbestos

Material Specification:

1e202, fscm 11083 mfr ref all material responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0