## NSN 5330-00-984-4749

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-00-984-4749
Cross Sectional Shape:
Solid single or composition
Hole Diameter:
Between 0.140 inches and 0.160 inches
Overall Length:
Between 1.300 inches and 1.360 inches
Overall Width:
Between 1.300 inches and 1.360 inches
Aperture Diameter:
Between 1.050 inches and 1.070 inches
Outside Corner Radius:
Between 0.140 inches and 0.220 inches
Center To Center Distance Between Bolt Holes Along Width:
Between 0.960 inches and 0.980 inches
Center To Center Distance Between Bolt Holes Along Length:
Between 0.960 inches and 0.980 inches
Outside Edge To Bolt Hole Center Distance Along Width:
0.180 inches
Outside Edge To Bolt Hole Center Distance Along Length:
Outside Edge To Bolt Hole Center Distance Along Length: 0.180 inches
0.180 inches
0.180 inches  Cross-sectional Thickness:
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:  4  Hardness Rating:
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:  4  Hardness Rating:  40.0 shore durometer a and 50.0 shore durometer a
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:  4  Hardness Rating:  40.0 shore durometer a and 50.0 shore durometer a  Material:
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:  4  Hardness Rating:  40.0 shore durometer a and 50.0 shore durometer a  Material:  Rubber butadiene-styrene class sbr
0.180 inches  Cross-sectional Thickness: Between 0.047 inches and 0.077 inches  Bolt Hole Quantity: 4  Hardness Rating: 40.0 shore durometer a and 50.0 shore durometer a  Material: Rubber butadiene-styrene class sbr  Material Specification:
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:  4  Hardness Rating:  40.0 shore durometer a and 50.0 shore durometer a  Material:  Rubber butadiene-styrene class sbr  Material Specification:  Mil-r-900 military specification single material response
0.180 inches  Cross-sectional Thickness:  Between 0.047 inches and 0.077 inches  Bolt Hole Quantity:  4  Hardness Rating:  40.0 shore durometer a and 50.0 shore durometer a  Material:  Rubber butadiene-styrene class sbr  Material Specification:  Mil-r-900 military specification single material response  Style Designator:
0.180 inches  Cross-sectional Thickness: Between 0.047 inches and 0.077 inches  Bolt Hole Quantity: 4  Hardness Rating: 40.0 shore durometer a and 50.0 shore durometer a  Material: Rubber butadiene-styrene class sbr  Material Specification: Mil-r-900 military specification single material response  Style Designator: Non-circular
0.180 inches  Cross-sectional Thickness: Between 0.047 inches and 0.077 inches  Bolt Hole Quantity: 4  Hardness Rating: 40.0 shore durometer a and 50.0 shore durometer a  Material: Rubber butadiene-styrene class sbr  Material Specification: Mil-r-900 military specification single material response  Style Designator: Non-circular  Shelf Life:

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-900 spec.