

View Online at <https://aerobasegroup.com/nsn/5330-00-998-3258>

**Cross Sectional Shape:**

Metal and synthetic rubber

**Hole Diameter:**

Between 0.228 inches and 0.234 inches

**Overall Length:**

Between 1.995 inches and 2.005 inches

**Overall Width:**

Between 1.830 inches and 1.835 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 0.995 inches and 1.005 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 1.495 inches and 1.505 inches

**Cross-sectional Thickness:**

0.165 inches

**Gage Ring Thickness:**

Between 0.122 inches and 0.128 inches

**Bolt Hole Quantity:**

4

**Elongation Percentage:**

125

**Hardness Rating:**

55.0 shore durometer a and 75.0 shore durometer a

**Special Features:**

To apertures, one 0.530 in. Dia, one, 0.310 in. Dia, 0.900 in. To 0.905 in. C t c along w

**Material:**

Aluminum alloy 6061 and rubber fluorosilicone class fq

**Material Specification:**

Qq-a-250/11 federal specification 1st material response and mil-r-25988, type 1, cl 1, gr 60 military specification 2nd material response or mil-r-25988, ty1, cl 1, gr 70 military specification 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-r-25988 spec.