

View Online at <https://aerobasegroup.com/nsn/5330-00-998-3258>

Cross Sectional Shape:

Metal and synthetic rubber

Hole Diameter:

Between 0.228 inches and 0.234 inches

Overall Length:

Between 1.995 inches and 2.005 inches

Overall Width:

Between 1.830 inches and 1.835 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.995 inches and 1.005 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.495 inches and 1.505 inches

Cross-sectional Thickness:

0.165 inches

Gage Ring Thickness:

Between 0.122 inches and 0.128 inches

Bolt Hole Quantity:

4

Elongation Percentage:

125

Hardness Rating:

55.0 shore durometer a and 75.0 shore durometer a

Special Features:

Two apertures, one 0.530 in. Dia, one, 0.310 in. Dia, 0.900 in. To 0.905 in. C t c along w

Material:

Aluminum alloy 6061 and rubber fluorosilicone class fq

Material Specification:

Qq-a-250/11 federal specification 1st material response and mil-r-25988, type 1, cl 1, gr 60 military specification 2nd material response or mil-r-25988, ty1, cl 1, gr 70 military specification 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-25988 spec.