

View Online at <https://aerobasegroup.com/nsn/5330-01-015-8799>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

0.500 inches

Overall Length:

3.812 inches

Overall Width:

3.812 inches

Aperture Diameter:

3.031 inches

Outside Corner Radius:

0.500 inches

Center To Center Distance Between Bolt Holes Along Width:

2.812 inches

Center To Center Distance Between Bolt Holes Along Length:

2.812 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.500 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.500 inches

Cross-sectional Thickness:

0.062 inches

Bolt Hole Quantity:

4

Hardness Rating:

70.0 shore durometer a and 85.0 shore durometer a

Criticality Code Justification:

Feat

Special Features:

As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from mercury contamination

Material:

Cork and rubber butadiene-acrylonitrile class nbr

Material Specification:

Mil-g-12803, f224000-2s9 military specification single material response

Special Test Features:

Special quality control testing

Style Designator:

Non-circular

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-g-12803 spec.