

View Online at <https://aerobasegroup.com/nsn/5330-01-024-2523>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

Between 0.260 inches and 0.300 inches

**Overall Length:**

5.690 inches

**Overall Width:**

5.320 inches

**Aperture Width:**

3.810 inches

**Aperture Length:**

4.940 inches

**Center To Center Distance Between Bolt Holes Along Width:**

4.560 inches

**Center To Center Distance Between Bolt Holes Along Length:**

4.940 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.380 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.380 inches

**Cross-sectional Thickness:**

0.125 inches

**Bolt Hole Quantity:**

4

**Hardness Rating:**

40.0 shore durometer a and 50.0 shore durometer a

**Criticality Code Justification:**

Zzzy

**Material:**

Rubber butadiene-styrene class sbr

**Material Specification:**

Mil-r-900 military specification single material response

**Special Test Features:**

Special quality control testing

**Style Designator:**

Non-circular

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-r-900 spec.