NSN 5330-01-029-7456

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-029-7456

Cross	Se	ction	nal	Sha	ne:
UI U33	OC.	CLICI	ıaı	ulia	vc.

Solid single or composition

Hole Diameter:

Between 0.271 inches and 0.291 inches

Overall Length:

Between 5.615 inches and 5.635 inches

Overall Width:

Between 7.990 inches and 8.010 inches

Inside Corner Radius:

Between 0.115 inches and 0.135 inches

Outside Corner Radius:

Between 0.115 inches and 0.135 inches

Aperture Width:

Between 6.990 inches and 7.010 inches

Aperture Length:

Between 4.615 inches and 4.635 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.240 inches and 1.260 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.271 inches and 1.291 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.240 inches and 0.260 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.240 inches and 0.260 inches

Cross-sectional Thickness:

Between 0.052 inches and 0.072 inches

Bolt Hole Quantity:

20

Material:

Rubber chloroprene class cr and asbestos

Material Specification:

Garlock no. 7228, fscm 00929 mfr ref single material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0