NSN 5330-01-032-6499

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-032-6499

| Cross Sectional Shape: |
|----------------------------------------------------------------------------------------------------------------------------------------------|
| Solid single or composition |
| Hole Diameter: |
| 0.438 inches |
| Tempurature Rating: |
| -80.0 degrees fahrenheit and 425.0 degrees fahrenheit |
| Bolt Circle Diameter: |
| 18.250 inches |
| Outside Diameter: |
| 20.000 inches |
| Aperture Diameter: |
| 15.000 inches |
| Cross-sectional Thickness: |
| 0.125 inches |
| Bolt Hole Quantity: |
| 20 |
| Hardness Rating: |
| 65.0 shore durometer a and 75.0 shore durometer a |
| Criticality Code Justification: |
| Zzzy |
| Material: |
| Rubber silicone class q |
| Material Specification: |
| Zz-r-765, cl 2b, grade 70 federal specification single material response |
| Special Test Features: |
| Special quality control testing |
| Style Designator: |
| Circular |
| Test Data Document: |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Reference Number Differentiating Characteristics: |
| As differentiated by material which must conform to ships parts control center special quality control provisions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |