NSN 5330-01-041-9718

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-041-9718

Cross	Se	ction	nal	Sha	ne:
UI U33	OC.	CLICI	ıaı	ulia	vc.

Solid single or composition

Hole Diameter:

Between 0.120 inches and 0.135 inches

Overall Length:

Between 1.180 inches and 1.195 inches

Overall Width:

Between 1.180 inches and 1.195 inches

Aperture Diameter:

Between 0.735 inches and 0.765 inches

Outside Corner Radius:

Between 0.060 inches and 0.090 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.901 inches and 0.911 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.901 inches and 0.911 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.134 inches and 0.147 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.134 inches and 0.147 inches

Cross-sectional Thickness:

Between 0.022 inches and 0.042 inches

Bolt Hole Quantity:

Hardness Rating:

55.0 shore durometer a and 70.0 shore durometer a

Material:

Rubber synthetic and cork

Material Specification:

Mil-c-6183 cl 2 gr b military specification single material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-c-6183 spec.