NSN 5330-01-124-1564

Gasket - Page 1 of 2

A032a0



View Online at https://aerobasegroup.com/nsn/5330-01-124-1564

| Cross Sectional Shape: |
|---|
| Solid single or composition |
| Hole Diameter: |
| 0.281 inches |
| Overall Length: |
| 9.250 inches |
| Overall Width: |
| 5.375 inches |
| Inside Corner Radius: |
| 0.750 inches |
| Aperture Width: |
| 4.125 inches |
| Aperture Length: |
| 8.000 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 2.500 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 3.000 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 1.437 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 1.625 inches |
| Cross-sectional Thickness: |
| Between 0.023 inches and 0.037 inches |
| Bolt Hole Quantity: |
| 10 |
| Special Features: |
| 0.312 inch distance from edge of gasket to center of bolt holes along length and width |
| Material: |
| Plastic polyamide and rubber butadiene-acrylonitrile class nbr or rubber synthetic |
| Material Specification: |
| Mil-c-8068 type 1, 2 or 3 military specification single material response |
| Style Designator: |
| Non-circular Section 1. The section |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

NSN 5330-01-124-1564

Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-c-8068 spec.