NSN 5330-01-124-5809

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-124-5809

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| Between 0.110 inches and 0.140 inches |
| Overall Length: |
| 1.312 inches |
| Overall Width: |
| 0.906 inches |
| Inside Corner Radius: |
| 0.453 inches |
| Aperture Width: |
| Between 0.521 inches and 0.541 inches |
| Aperture Length: |
| 0.531 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 0.985 inches and 1.015 inches |
| Cross-sectional Thickness: |
| Between 0.015 inches and 0.047 inches |
| Hardness Rating: |
| 40.0 shore durometer a and 50.0 shore durometer a |
| Material: |
| Rubber butadiene-styrene class sbr |
| Material Specification: |
| Mil-r-900 military specification single material response |
| Style Designator: |
| Ular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| Mil-std (military Standard): |
| Mil-r-900 spec. |
| |