## NSN 5330-01-127-8582

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-01-127-8582

| Cross Sectional Shape:  |
|---|
| Solid single or composition   |
| Hole Diameter:  |
| 0.310 inches  |
| Overall Length:   |
| 13.000 inches   |
| Overall Width:  |
| 7.620 inches  |
| Inside Corner Radius:   |
| 0.190 inches  |
| Outside Corner Radius:  |
| 1.250 inches  |
| Aperture Width:   |
| 5.500 inches  |
| Aperture Length:  |
| 10.880 inches   |
| Center To Center Distance Between Bolt Holes Along Width:   |
| 3.250 inches  |
| Center To Center Distance Between Bolt Holes Along Length:  |
| 4.000 inches  |
| Outside Edge To Bolt Hole Center Distance Along Width:  |
| 2.185 inches  |
| Outside Edge To Bolt Hole Center Distance Along Length:   |
| 2.500 inches  |
| Cross-sectional Thickness:  |
| 0.060 inches  |
| Bolt Hole Quantity:   |
| 10  |
| Hardness Rating:  |
| 60.0 shore durometer a and 70.0 shore durometer a   |
| Special Features:   |
| 0.435 inch distance from edge of gasket to bolt hole center along width 0.440 inch distance from edge of gasket to bolt hole center along |
| length  |
| Material:   |
| Rubber chloroprene class cr   |
| Material Specification:   |
| Mil-g-1149, type 2 military specification single material response  |
| Style Designator:   |
| Non-circular Section 1997   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

\_\_

## NSN 5330-01-127-8582

Gasket - Page 2 of 2



| Dem |  |  |  |
|-----|--|--|--|
|     |  |  |  |
|     |  |  |  |

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-g-1149 spec.