

View Online at <https://aerobasegroup.com/nsn/5330-01-132-1096>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

0.281 inches

**Overall Length:**

3.500 inches

**Overall Width:**

3.250 inches

**Aperture Width:**

2.625 inches

**Aperture Length:**

2.875 inches

**Inside Corner Bevel Length Along Width:**

0.500 inches

**Inside Corner Bevel Length Along Length:**

0.500 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

2.875 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

0.312 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

0.312 inches

**Cross-sectional Thickness:**

0.062 inches

**Bolt Hole Quantity:**

4

**Hardness Rating:**

45.0 shore durometer a and 55.0 shore durometer a

**Criticality Code Justification:**

Zzzy

**Special Features:**

Item must comply with requirements of defense supply center philadelphia production standard no. P00422nrp

**Material:**

Rubber chloroprene class cr

**Material Specification:**

Mil-g-1149, type 1 military specification single material response

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Reference Number Differentiating Characteristics:**

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-g-1149 spec.